

LTB2 chargers

	EPN		
	CT024S015UMP020	CT024S030UMP020	CT024S060UMP020
Model	24V 15A	24V 30A	24V 60A
Nominal voltage	24 V	24 V	24 V
Output current	15 A	30 A	60 A
Mains voltage supply	220-240 V	220-240 V	220-240 V
Mains cable dimensions	3x1,5 mm ²	3x1,5 mm ²	3x1,5 mm ²
Mains cable length	2,5 m	2,5 m	2,5 m
Mains connector (included)	10A Schuko	10A Schuko	10A Schuko
Battery cable	2x8 mm ²	2x8 mm ²	2x10 mm ²
Battery cable length	2 m	2 m	2 m
Battery connector (not included)	User defined	User defined	User defined
Ingress Protection	IP20	IP20	IP20
Ambient temperature range (at full capacity)	-5 to +40°C	-5 to +40°C	-5 to +40°C
Ambient max. temp. (with reduced capacity)	50°C	50°C	50°C
Cooling	Fan	Fan	Fan
Short Circuit protection	Yes	Yes	Yes
Wrong polarity protection	Electronic	Electronic	Electronic
Certifications	CE	CE	CE
Status LED	Yes	Yes	Yes
Charger weight excl. cables	1,5 kg	1,5 kg	2,3 kg
Charger weight incl. cables	2,1 kg	2,1 kg	3,1 kg
Dimensions (HxWxD)	243x112x74 mm	243x112x74 mm	295x138x89 mm
Drive away protection*	Yes	Yes	Yes

*DAP for chargers included but for batteries to be ordered separately

24V 15A & 24V 30A



24V 60A

