

LOKITHOR

LOKITHOR

LiFePO4 Jump Starter

J1350 PRO 12V 1350A | 6.5L 3.5L
Gas Diesel



- Car / MPV
- Motorboat
- Motorcycle
- SUV
- Truck
- UTV / ATV
- Smartphone
- Tablet
- Camera

SPECIFICATIONS

Model	J1350 PRO	Capacity	2000mAh 25.6Wh LiFePO4
Nominal Voltage	12.8V	Starting Voltage	12V
Starting Current	700Amp	Peak Current	1350Amp
Polarity	Red (+), Black (-)	USB-A Output	5V=3A, 9V=2A, 12V=1.5A (18W MAX)
Suitable Engine Displacement	Up to 6.5L gasoline and 3.5L diesel 12V engines	USB-C Input & Output	5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A (PD 30W MAX)
Charging Temperature	0°C to 45°C	Service life	>2000 cycles (in good condition)
Storage Temperature	-20°C to 50°C	IP Rating	IP 65 (w/ Ports closed)
Operation Temperature	-20°C to 60°C	Product Dimensions (L*W*H)	202*92*45mm
LED Lumen	200 lumens	Package Dimensions (L*W*H)	239*129*83.5mm
Unit Weight	0.64kg	Unit Weight w/Clamps & Accessories	1.25kg

FEATURES



CONNECTMAX TECHNOLOGY

Our state-of-the-art system automatically detects the impedance of the clamp connection to your car battery, ensuring optimal contact every time and maximizing the starting efficiency of your jump starter.



LIFEPO4 SAFE PERFORMANCE

Lokithor's Lithium Iron Phosphate (LiFePO4) battery technology offers safe and stable chemical performance with a long cycle life.



MULTIPLE PROTECTIONS

Overvoltage & Undervoltage & Overcurrent
High temperature & Low temperature
Short circuit & Reverse connection

CE FC UN38.3 RoHS UK CA IP65

WHAT'S IN THE BOX



Physical Product



Manual




USB - C To USB - C Wire



USB - A To USB - C Wire



Accessories Storage Bag



Jump Starter Clamps



J1350 PRO

CONTACT US

Grepow Inc.
290 Lindbergh Ave
Livermore, CA 94551
United State

✉ service@lokithor.net

Genspow GmbH
Ottostr.11
41352 Korschenbroich
Germany

🌐 WWW.LOKITHOR.NET

