12V 3Ah NLP9



INSANE PERFORMANCE.
LITHIUM POWERSPORT BATTERY.™

2X 10X 5X MORE POWER. MORE STARTS. LONGER LIFE.

DYNAMIC BMS.

Equipped with an auto-enabled, advanced battery management system that provides maximum protection, performance, and bi-directional cell equalization for long-lasting stability. No BMS reset needed.

ACTIVE PROTECTION.

Protects against over-charge, extreme-heat, short-circuit, over-discharge, extreme-cold, and over-current.

SHOCK ABSORBTION.

Designed with a custom rubber dampening base and foam inserts to extend the life of the battery and keep connections secure.



30339 Diamond Parkway, #102 Glenwillow, OH 44139 | USA 1.800.456.6626

no.co



UNIVERSAL MOUNTING.

Modular spacers can be added to alter the size and allow the battery to be safely and securely mounted. A removable mounting block allows the battery to fit more applications. The threaded insert enables direct-mounting for additional simplicity and security.





FEMALE.





SIDE.

TOP.





MULTI-CONNECTION TERMINALS.

Equipped with premium IP66 waterproof copper PCB plates. NLP Terminals can be mounted from the front, side, or top, and can be removed altogether depending on the application.



RAPID RECHARGE.

Use the Lithium mode on a Genius charger to fully recharge an NLP battery in minutes. See Genius models and charging times below.

180 Minutes

90 Minutes

36 Minutes

N/A

COMPATABLE SIZES.

n	α	SIZES	YUASA	OIZEO	CTV	Sizes
ĸ	1-1		AIIV		- I X	VI/FV
u	UI.	UILLU	IUAUA	UILLU	LIA	JILLJ

BTX7A-BS	YTX9
BTX9-BS	YTX7A-BS
BTR9-BS	YTX9-BS
BTX5L-BS	

BTX7L-BS

ETX9 BS SS



TECHNICAL SPECIFICATIONS

RECHARGE TIME

GENIUS1

GENIUS2

GENIUS5

GENIUS10

BCI SIZE:		9	
CHEMISTRY:	Lithium Iron Pho	osphate (LiFePO4	
NOMINAL VOLTAGE:	1	2.8	
AMP-HOURS:		3	
WATT-HOURS (WH):	3	8.8	
STARTING CURRENT:	4	100	
CHARGING Voltage (V):	14	4.6V	
CHARGING CURRENT (A):	9A	(Max)	
OPERATING TEMPERATURE:	-20°C	to 60°C	
CHARGING TEMPERATURE:	-10°C	to 50°C	
STORAGE TEMPERATURE:	-20°C	-20°C to 60°C	
WEIGHT:	2.29 lbs (1.03 kg)		
VOLUMETRICS:	Retail Packaging: Dimensions: 6.18" x 4.84" x 4.77"	Master Carton: Dimensions: 13.50" x 6.18" x 10.63"	

Weight: 3.17 lbs UPC: 0-46221-19007-6

Dimensions: 6.02" x 4.37" x 5.04"


Inner Carton:

WHAT'S IN THE BOX	
3.4" (85mm) (113mm) 4.5"	2.8" (70mm) LxWxH Minimum. 5.9" x 3.4" x 3.8" (149mm x 87mm x 96mm) LxWxH Maximum. 5.9" x 3.4" x 4.3" (149mm x 87mm x 108.5mm)

*Accessories not to scale with NLP9







30339 Diamono Glenwillow, OH 1.800.456.662

30339 Diamond Parkway, #102 Glenwillow, OH 44139 | USA 1.800.456.6626



Quantity: 6 UCC: 10046221190073

Units Per Pallet: 324 Units